



Decorators' White Paint

- for interior walls and ceilings
- well-covering, breathable interior wall paint



Application rate	Ca. 1 l/7 m ² . Determine the exact coverage by applying a test coat to the object
Areas of use	■ For mineral substrates (e.g. masonry, concrete, plaster) and construction slabs, wallpaper and old dispersion coatings
Property profile	■ Wet abrasion resistance class III DIN EN 13300 and hiding power class II DIN EN 13300 at 7 m ² per litre
Directions	Substrates must be clean, dry, free of grease and capable of supporting a load; remove loose parts Wash off distemper and chalking substrates Use primer to strengthen sanding and absorbent substrates Surface dry after approx. 2-3 hours, can be painted over after approx. 6 hours
Notes	The standard safety measures must be observed even when using low-pollutant paints and varnishes Please secure the container against falls and spills during transport.
Tools / Cleaning	Brush, paint roller, airless spraying equipment Clean the tools immediately after use with warm water and household cleaner, if necessary
Storage / Shelf life	Store in the sealed original container in a cool, dry, and frost-free place. Can be used for at least 1 year after the date of purchase Keep containers tightly closed and store upright to prevent spillages
Disposal	P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
VOC content as per the "Decopaint" Directive (2004/42/EC)	EU limit value for the product (Cat. A/a): max. 30 g/l (2010). This product contains < 1 g/l VOC.
Precautionary statements / Hazard statements	Contains 1,2-benzisothiazol-3(2H)-one, 2-methyl-2H-isothiazol-3-one. May produce an allergic reaction. Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
Precautionary statements / Hazard statements	