



Beeswax Stain

- for all types of wood indoors
- wood finishing based on renewable raw materials

Areas of use

- For all indoor wood types, e.g. furniture, wall and ceiling panelling

Directions

The substrate must be clean, dry and dust-free.
Sand with 150-180 grain sandpaper
Permissible wood moisture: 8-12 %
Risk of self-ignition (DGUV Information 209-046). May not be used at the same workspace as varnishes or stains containing nitrocellulose, collect and dispose of contaminated textiles (e.g. cleaning cloths, work clothes) in fire-resistant waste containers
When applying two coats, sand lightly in between with an abrasive sponge or sandpaper with grit size 240-320
Drying (at +20°C and 65 % rel. humidity): Approx. 12 hours

Notes

For priming, dilute with approx. 25% water

Storage / Shelf life

Store in the sealed original container in a cool, dry, and frost-free place. Can be used for at least 1 year after the date of purchase
The storage temperature should be between +5 and +35°C

Disposal

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Biocidal Products Regulation

Contains a biocidal product (in-can preservative) with the biocidal agents CMIT/MIT (3:1) for protecting the container content from deterioration by microbial organisms (germs, yeast, etc.). Please note the processing guidelines carefully!

VOC content as per the "Decopaint" Directive (2004/42/EC)

EU limit value for the product (Cat. A/e): max. 130 g/l (2010).
This product contains < 130 g/l VOC.

Precautionary statements / Hazard statements

1,2-benzisothiazol-3(2H)-one reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) Contains. May produce an allergic reaction. Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.,

Precautionary statements / Hazard statements