



## Universal Paint for Long-Term Protection

- for wood, masonry and much more
- versatile, high-opacity weather protection paint



### Areas of use

- For timber facing, framework, timer houses, shingles and fences
- For roof tiles, concrete, render, masonry and Eternit panels (preliminary coating may be required)

### Possible system products

- **Wood Sealing Primer (8919)**

### Directions

The substrate must be clean, dry and stable  
Pre-treat untreated exterior wood with a wood preservative (use wood preservatives safely. Always read the label and product information before use.)  
For light colour shades, an interim coat with a wood insulating primer is required to avoid the appearance of marks due to the wood components  
Reinforce sandy and absorbent substrates using a deep penetrating primer (this may contain preservatives, if necessary)  
Sand grey and weathered wood surfaces down to sound, bright wood.  
Stir well and apply quickly using a brush or roller.  
Apply a second coat once the first has dried.  
Dilution with water (max. 10%) if necessary  
Drying: approx. 2-4 hours. Paint film fully hardened after approx. 2 weeks  
Application temperature: +5°C to +25°C  
Protect the fresh coat from rain  
Seal opened containers well and use contents as soon as possible.

### Notes

Not suitable for wooden floors or areas with foot traffic.  
On planed larch and softwoods with a high resin content, the coating may have reduced adhesion and resistance to weathering. This is especially the case on horizontal year rings, knots and areas of winter growth that are high in resin. Maintenance and renovation must be carried out more frequently on these surfaces. The only remedy for this is pre-weathering or very coarse sanding (P80). If these wood types are rough-sawn, considerably longer maintenance and renovation intervals are to be expected.  
Check colour, adhesion and compatibility with the substrate by setting up a trial area.

### Tools / Cleaning

Apply with roller and brush

### Storage / Shelf life

Store in the sealed original container in a cool, dry, and frost-free place. Can be used for at least 1 year after the date of purchase

### Disposal

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

### Biocidal Products Regulation

Contains a biocidal product (in-can preservative) with the biocidal agents CMIT/MIT (3:1) for protecting the container content from deterioration by microbial organisms (germs, yeast, etc.). Please note the processing guidelines carefully!

### Safety advice

Keep out of the reach of children.  
Use an A2/P2 combi-filter when spraying.  
Use a P2 dust filter when grinding or sanding.  
Ensure the area is thoroughly ventilated during application and drying.  
Do not eat, drink or smoke while using the paint.  
In the event of contact with the eyes or skin, rinse out thoroughly and immediately with water.  
Do not allow it to enter the ground, the sewage system or any bodies of water.  
Clean tools with soapy water immediately after use.  
Only send fully emptied containers for recycling.  
Take any leftover liquid material to the collection point for waste paint.

VOC content as per the  
"Decopaint" Directive  
(2004/42/EC)

EU limit value for the product (cat A/d): max. 130 g/l (2010).  
This product contains < 130 g/l VOC.

---

Precautionary statements /  
Hazard statements

Contains 1,2-benzisothiazol-3(2H)-one, reaction mass of 5-chloro-2- methyl-2H-isothiazol-3-one and 2-  
methyl-2H-isothiazol-3- one (3:1). May produce an allergic reaction. Warning! Hazardous respirable  
droplets may be formed when sprayed. Do not breathe spray or mist.

---

Precautionary statements /  
Hazard statements